

PC BASE DVR

- *EZ-6448
- *EZ-4848
- *EZ-3248
- *EZ-3296

Feature:

- Free Central Monitoring Program (DVMS)
- GUI with Multi Language menu A13
(including English, Italian, Russian, Spanish, French, Turkish, etc)
- 480fps REAL TIME recording Speed
- 64ch Video Input, 16ch (Option)Audio Recording (EZ-6448)
- 48ch Video Input, 16ch (Option)Audio Recording (EZ-4848)
- 32ch Video Input, 16ch (Option)Audio Recording (EZ-3248)
- TRIPLEX, Simultaneous Record, Playback, Display and remote Access
- Remote Live-View, Playback, Configuration and PTZ Control through Network
- Remote AUDIO listening & playback
- Direct CD, DVD writing without using additional burning software
- Joystick control for PTZ of Speed Dome Camera
- MPEG-4 Compression
- A variety of Recording modes
(Continuous, Motion detection, Sensor, Schedule)
- Virtual Keyboard



PC Desktop



Rack Mount

Specification

Description		EZ-6448 (EZ-1624 x 4)	EZ-4848 (EZ-1624 x 3)	EZ-3248 (EZ-1624 x 2)	EZ-3296
Video Input		64ch	48ch	32ch	32ch
Audio Input		Max. 16ch	Max. 16ch	Max. 16ch	Max. 16ch (option)
Display Speed	NTSC	Real-Time (16A,16B,16C, 16D)	Real-Time (16A,16B,16C)	Real-Time (16A, 16B)	960fps
	PAL	Real-Time (16A,16B,16C, 16D)	Real-Time (16A,16B,16C)	Real-Time (16A,16B)	800fps
Multi-screen Display		1,4,7,9,10,13, 16A, 16B, 16C, 16D	1,4,7,9,10,13, 16A, 16B, 16C	1,4,7,9,10,13, 16A, 16B	1,4,7,9,10,13, 16, 25, 32
Total Recording Speed	NTSC	360x240	Max. 480 fps	Max. 480 fps	Max. 480 fps
		720x240	Max. 240 fps	Max. 240 fps	Max. 240 fps
		720x480	Max. 120 fps	Max. 120 fps	Max. 120 fps
	PAL	360x288	Max. 400 fps	Max. 400 fps	Max. 400 fps
		720x288	Max. 200 fps	Max. 200 fps	Max. 200 fps
	720x576	Max. 100 fps	Max. 100 fps	Max. 100 fps	
TV Output		4ch (16A, 16B, 16C, 16D)	3ch (16A, 16B, 16C)	2ch (16A, 16B)	1ch
Looping output		64ch	48ch	32ch	32ch
Sensor / Control		4,8,12,16 Expandable			
Compression		MPEG-4			
Compressed Image Size		Average 2KB (360x240, Standard Quality)			
Recording Mode		Continuous, Event(Motion, Sensor), Pre/Post-Alarm, Schedule (Camera, Time, Date)			
Searching Option		Date, Time, Thumbnail Preview, Event, Object Search			
PTZ Control		RS-422 Interface			
Remote Control		Live View & Audio, search, Setup, PTZ control via TCP/IP, ISDN, PSTN (WebBrowser Viewing)			
System Watchdog		Automatic reset of recorder upon detecting system conflicts			
Watermarking		Fully authenticated by watermarking software (Optional)			
OS Platform		Windows XP Professional (Hyper-Threading)			
Hardware Specification Recommended	M/B	Intel or ASUS			
	CPU	P4 3.0 GHz (INTEL, Hyper-Threading)			
	VGA	ATI 128MB			
	RAM	1 GB			512 MB

* Max. Recording Speed is based on CPU specification recommended.